Premium Hortshade[®] Medium



Product Profile

Shadecloth Range

Rev.5 05/13

Product Description

Premium Hortshade® Medium is a high quality medium-duty knitted shadecloth available in a range of colours and supplied in bulk rolls for a wide range of industrial, horticultural and agricultural applications.

Material

Yarn UV stabilised HDPE Construction Monofilament yarn Pattern Lock-stitch knitted Temperature range -30°C to +75°C

Features

- Meets Australian standard AS 4174 1994 Synthetic Shadecloth.
- 10 year UV warranty on fabric.
- Strong HDPE fabric won't rot or absorb moisture.
- 100% recyclable material
- 100% Lead and Phthalate Free
- Greenguard® and Oeko-Tex® certified

Usage Instructions

- Fabric is not flame proof.
- Contact with chemicals and/or pesticides that contain sulphur, halogens or highly acidic substances may reduce the service life of the fabric and void the warranty.

Properties

Nominal fabric mass $250 \text{ gsm} \pm 20$ (AS 2001.2.13) Approximate thickness 1.18mm

Performance

Tensile Strength - Warp 591 N/50mm Elongation at break 60.8 % Tensile Strength - Weft 1485 N/50mm Elongation at break 54.7 % (AS 2001.2.3) Wing Tear – Warp (mean) 113 N (AS 2001.2.10) Wing Tear – Weft (mean) 196 N (AS 2001.2.10) Bursting Pressure (mean) 2450 kPa (AS 2001.2.4) Bursting Force (mean) 1170 N (AS 2001.2.19)

Flammability

(AS 1530.2)

Flammability index (range 0-100)

22

Suggested Specification

Shadecloth fabric shall be compliant to AS 4174 and shall be Synthesis Premium Hortshade Medium knitted HDPE monofilament shade fabric.

Colour	Code	Nom. Width	Length	Cover Factor	Av. % Transmis.	Shade Factor	Av. UVR Transmis.	AV. PAR Transmis.	% UVR Block
Forest Green Black White Beige	429003 428983 429010 428990	1.83 m	50 m	68% 68% 66% 67%	35% 33% 62% 48%	65% 67% 38% 52%	33% 33% 35% 35%	35% 33% 70% 51%	67% 67% 65% 65%
Forest Green Black White Beige	429041 429027 429058 429034	3.66 m (Folded)	50 m	68% 68% 66% 67%	35% 33% 62% 48%	65% 67% 38% 52%	33% 33% 35% 35%	35% 33% 70% 51%	67% 67% 65% 65%

1.83 m 3.66 m Tested according to AS 4174 Synthetic Shadecloth Approx. roll weight: 22 kg 43.5 kg Av. % Transmis. Approx. roll diameter: 0.28 m 0.40 m Core diameter:

35 mm

35 mm

= Average % Transmission within the 290-770nm spectrum Av. UVR Transmis. = Average % Transmission within the 290-400nm spectrum Av. PAR Transmis. = Average % Transmission within the 408-770nm spectrum

The above results are typical averages from quality assurance testing and are not to be taken as a minimum specification nor as forming any contract between Gale Pacific and another party. Due to continuous product improvement, Product Profiles are subject to alteration without notice.

Notice: As the use and disposal of this product are beyond Gale Pacific's control, regardless of any assistance provided without charge, Gale Pacific assumes no obligation or liability for the suitability of its products in any specific end use application. It is the customer's responsibility to determine whether Gale Pacific's products are appropriate for the specific application and complies with any legal & patent regulations.

FOR MORE INFORMATION - PLEASE CONTACT:

Gale Pacific Ltd. PO Box 892, Braeside, Victoria, 3195 Phone +61 3 9518 3399 Fax +61 3 9518 3398 Australia ΝZ Gale Pacific (NZ) Ltd. PO Box 65 527, Mairangi Bay, Auckland Phone +64 3 373 9500 Fax +64 3 373 9501 UAE Gale Pacific FZE. PO Box 17696, Jebel Ali, Dubai Phone +971 4 881 7114 Fax +971 4 881 7167 Gale Pacific Inc. Suite 1704, 285 W. Central Parkway, Altamonte USA Phone +1 407 772 7979 Fax +1 407 772 0553

Springs, Florida, 32714